

## MATERIAL SAFETY DATA SHEET

### 1. PRODUCT IDENTIFICATION

**TRADE NAME (AS LABELED):** TILE GUARD™ ONE STEP GROUT SEALER WALL & COUNTER  
**PRODUCT CODES:** 93217, 93217-30  
**PRODUCT USE:** Grout Sealer  
**SUPPLIER/MANUFACTURER'S NAME:** HOMAX PRODUCTS, INC.  
**ADDRESS:** 200 Westerly Rd.  
 Bellingham, WA 98226  
**BUSINESS PHONE:** 1-800-729-9029  
**CHEMTREC EMERGENCY NO.:** 1-800-424-9300 (United States)  
 1-703-527-3887 (International Collect)  
**DATE OF PREPARATION:** May 10, 2010

This product is sold to consumers for household use in containers of relatively small volume (i.e. 5 gallon or less in size). This MSDS has been developed to address safety concerns affecting those individuals working in warehouses and other places where large numbers of these containers are stored, as well as those affecting potential users of this product in industrial /occupational settings. All pertinent health, safety and environmental information have been presented in this document, per the requirements of the US Federal OSHA Hazard Communication Standard (29 CFR 1910.1200).

### 2. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	% w/w	EXPOSURE LIMITS IN AIR						
			ACGIH-TLV		OSHA-PEL		NIOSH-REL		
			TWA	STEL	TWA	STEL	TWA	STEL	IDLH
			mg/m <sup>3</sup>	mg/m <sup>3</sup>	mg/m <sup>3</sup>	mg/m <sup>3</sup>	mg/m <sup>3</sup>	mg/m <sup>3</sup>	mg/m <sup>3</sup>
Hydrocarbon Solvent	Proprietary	75 - 85	1370	NE	2000	NE	350	C 1800	NE
Liquefied Petroleum Gas	68476-86-8	5 - 15	4508	NE	1800	NE	1800	NE	2100
Butyl acetate	123-86-4	1 - 5	150 ppm	NE	710	NE	NE	NE	NE
Sealant polymer	Proprietary	< 1	NE	NE	NE	NE	NE	NE	NE
Water and ingredients present in concentrations of less than 1% (or less than 0.1% if carcinogens)		Balance	The ingredients in the balance of this product do not contribute significant hazards beyond those described in this document. All pertinent health, safety and environmental information has been presented, per the requirements of the US Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canadian WHMIS.						

NE = Not Established. See Section 16 for Definitions of Terms Used.

NOTE (1): ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-1998 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

### 3. HAZARD IDENTIFICATION

#### EMERGENCY OVERVIEW:

**PHYSICAL DESCRIPTION:** This product is a clear liquid with a floral scent in an aerosol can.

**HEALTH HAZARD:** This product can cause irritation to the eyes or skin. This product is harmful if swallowed or inhaled. If vapors, mists or particulates of this product are inhaled, irritation of the nose or throat could occur. Overexposure of vapors or spray mist can be harmful to lungs.

**FIRE HAZARD:** This product is extremely flammable. Vapor can cause flash fire.

**REACTIVITY HAZARD:** This product is stable under ordinary conditions of use and storage.

**ENVIRONMENTAL HAZARD:** This product does not normally present a significant hazard to aquatic or terrestrial life in consumer quantities.

#### SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE:

The most significant route of occupational overexposure is inhalation of vapors or spray mist. The symptoms of overexposure to this product are as follows:

**INHALATION:** Vapors, mists, sprays, or dusts of this product can cause irritation to the respiratory tract. High concentrations of Hydrocarbon solvent and liquid components of this product can cause central nervous system depression, headache, nausea, dizziness, confusion, unconsciousness, lung damage, coma, and death.

**CONTACT WITH SKIN or EYES:** Contact can cause eye or skin irritation. Prolonged skin contact can result in dermatitis. Prolonged eye exposure may include redness, pain, and tearing.

**SKIN ABSORPTION:** No component of this product is reported to be absorbed through intact skin.

**INGESTION:** If the product is swallowed, irritation of the mouth, throat, and other tissues of the gastro-intestinal system can occur. Ingestion of large amounts can cause irritation, pain, vomiting, and diarrhea.

**CHRONIC:** Long-term skin or eye contact can result in dermatitis or eye irritation. Over exposure could cause adverse effects to liver and kidney.

**TARGET ORGANS:** Acute: Eyes, skin, lungs, central nervous system and gastrointestinal tract. Chronic: Kidneys and liver.

#### **Hazardous Materials Identification System (HMIS)**

<b>Health</b>	<b>1</b>
<b>Flammability</b>	<b>4</b>
<b>Physical Hazard</b>	<b>1</b>

---

#### **4. FIRST-AID MEASURES**

Victims of chemical exposure must be taken for medical attention if any adverse effects occur. Take a copy of label and MSDS to physician or health professional with victim.

**SKIN EXPOSURE:** If this product contaminates the skin, immediately begin decontamination with running water. Remove exposed or contaminated clothing, taking care not to contaminate eyes. Victim must seek immediate medical attention if any adverse exposure symptoms develop.

**EYE EXPOSURE:** If this product enters the eyes, open victim's eyes while under gently running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 15 minutes. Victim must seek medical attention.

**INHALATION:** If vapors, mists, or sprays of this product are inhaled, remove victim to fresh air. Victim must seek immediate medical attention if any adverse exposure symptoms develop. If necessary, use artificial respiration to support vital functions.

**INGESTION:** If this product is swallowed, **CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. DO NOT INDUCE VOMITING**, unless directed by medical personnel. Have victim rinse mouth with water, if conscious. Never induce vomiting or give a diluent (e.g., water) to someone who is unconscious, having convulsions, or unable to swallow. If contaminated individual is convulsing, maintain an open airway and obtain immediate medical attention.

---

#### **5. FIRE-FIGHTING MEASURES**

**FLASH POINT:** < 0 °F (Propellant)

**AUTOIGNITION TEMPERATURE:** Not applicable.

**FLAMMABLE LIMITS (in air by volume, %):**

Lower: 2.2 %

Upper: 9.5 %.

**FIRE EXTINGUISHING MATERIALS:** Use extinguishing material suitable to the surrounding fire.

Water Spray: NO

Carbon Dioxide: OK

Foam: OK  
Halon: OK

Dry Chemical: OK  
Other: Any "ABC" Class.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** When involved in a fire, this material may decompose and generate irritating fumes and toxic gases (e.g., Carbon monoxide and Carbon dioxide).

**Explosion Sensitivity to Mechanical Impact:** Not sensitive under normal conditions.

**Explosion Sensitivity to Static Discharge:** Not sensitive under normal conditions.

**SPECIAL FIRE-FIGHTING PROCEDURES:** Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Move containers from fire area if it can be done without risk to personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. Isolate from incompatible chemicals (see Section 10, Stability and Reactivity), heat, sparks, electrical equipment, and open flame.

---

## 6. ACCIDENTAL RELEASE MEASURES

**SPILL AND LEAK RESPONSE:** Trained personnel using pre-planned procedures should respond to uncontrolled releases. Proper protective equipment should be used. In case of a spill, clear the affected area and protect people.

**RESPONSE TO INCIDENTAL RELEASES:** Personnel who have received basic chemical safety training can generally handle small-scale releases, such as 1 container of this product. Respond to incidental chemical releases by wearing gloves, goggles, and appropriate body protection.

**RESPONSE TO NON-INCIDENTAL RELEASES:** Respond to non-incident chemical releases of this product, such as the simultaneous puncturing of several containers, by clearing the impacted area and contacting appropriate emergency personnel. Clean up should only be done by qualified personnel. Responders should wear the level of protection appropriate to the type of chemical released, the volume of the material spilled, and the location where the incident has occurred. Minimum Personal Protective Equipment should be Level B: triple-gloves, chemical resistant apron, boots, and splash goggles and Self-Contained Breathing Apparatus. Level B should also be used when oxygen levels are below 19.5% or are unknown.

**RESPONSE EQUIPMENT AND PROCEDURES:** Absorb spilled liquid with polypads or other suitable absorbent materials. Decontaminate the area thoroughly. Prevent spill rinsate from contamination of storm drains, sewers, soil or groundwater. Place all spill residues in a suitable container and seal. Dispose of in accordance with applicable U.S. Federal, State, or local procedures or appropriate standards of Canada (see Section 13, Disposal Considerations).

---

## 7. HANDLING and STORAGE

**WORK PRACTICES AND HYGIENE PRACTICES:** As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after using this product. Do not eat or drink while using this material. Avoid generating dusts, mists or sprays of this product. Remove contaminated clothing immediately.

**STORAGE AND HANDLING PRACTICES:** All employees who handle this material should be trained to use it safely. Open containers carefully on a stable surface. Empty containers can contain residual material; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store away from incompatible materials (see Section 10, Stability and Reactivity). Keep container tightly closed when not in use. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged. Control possible sources of ignition.

**PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely if necessary. Collect all rinsates and dispose of according to applicable U.S. Federal, State, or local procedures or appropriate Canadian standards.

**NFPA 30B:** Level 3 Aerosol

---

## 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

**VENTILATION AND ENGINEERING CONTROLS:** Use with adequate ventilation to prevent inhalation of vapors and spray mists. Ensure exposure levels are maintained below the limits provided in Section 2 (Composition and Information on Ingredients).

**RESPIRATORY PROTECTION:** If adequate ventilation can not be guaranteed, use NIOSH approved respirators to control dusts, mists, fumes or vapors. Maintain airborne contaminate concentrations below guidelines listed in Section 2 (Composition and Information on Ingredients). Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres use of a full-face-piece pressure/demand SCBA or a full face-piece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (29 CFR 1910.134).

**EYE PROTECTION:** For consumer use, wearing eye protection (such as splash goggles) is advisable. However, for specific industrial applications, enhanced eye protection can be necessary. Use approved safety goggles or safety glasses, as described in OSHA 29 CFR 1910.133. If necessary, refer to U.S. OSHA 29 CFR 1910.133, or appropriate Canadian standards.

**HAND PROTECTION:** For consumer use, wearing protective gloves is suggested. For specific industrial applications, wear chemical impervious gloves (e.g., Neoprene or Nitrile). If necessary, refer to U.S. OSHA 29 CFR 1910.138 or the appropriate standards of Canada.

**BODY PROTECTION:** For consumer use, no specific body protection is normally needed. For specific industrial applications, body protection is not normally needed. Use body protection appropriate for task (e.g., Tyvek suit, rubber apron). If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects can pierce the soles of the feet or where employee's feet can be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

---

## 9. PHYSICAL and CHEMICAL PROPERTIES

**RELATIVE VAPOR DENSITY (air = 1):** > 1

**SPECIFIC GRAVITY:** 0.7

**SOLUBILITY IN WATER:** Insoluble

**VAPOR PRESSURE, mmHg @ 20°C:** Not available

**ODOR THRESHOLD:** Not applicable

**COEFFICIENT OF OIL/WATER DISTRIBUTION (PARTITION COEFFICIENT):** Not applicable

**APPEARANCE, ODOR AND COLOR:** This product is a clear liquid with a floral scent in an aerosol can.

**EVAPORATION RATE (BuAc =1):** < 1 (n-Butyl Acetate = 1)

**MELTING/FREEZING POINT:** Not applicable

**BOILING POINT:** > 325 °F (>163 °C)

**pH:** Not applicable

---

## 10. STABILITY and REACTIVITY

**STABILITY:** Stable under normal circumstances of use and handling.

**DECOMPOSITION PRODUCTS:** Thermal decomposition of this product may generate irritating fumes and toxic gases (e.g., Carbon monoxide and Carbon dioxide).

**MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:** This product is not compatible with powerful oxidizers.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid contact with incompatible chemicals, heat, and all sources of ignition.

---

## 11. TOXICOLOGICAL INFORMATION

**TOXICITY DATA:** There are currently no toxicity data available for this product; the following toxicology information is available for components greater than 1% in concentration.

**The following data are available for the Hydrocarbon solvent (analogous compound):**

Eye effects-Human 880 ppm/15M

Inhalation-Rat LC<sub>50</sub>:3400 ppm/4H

Intravenous-Mouse LD50:40 mg/kg

**The following data are available for Liquefied Petroleum Gas:**

This is a simple asphyxiant.

**SUSPECTED CANCER AGENT:** The following table summarizes the carcinogenicity listing for the components of this product. "NO" indicates that the substance is not considered to be, or suspected to be, a carcinogen by the listed agency.

CHEMICAL	IARC	NTP	OSHA	ACGIH	PROP 65
Hydrocarbon solvent	NO	NO	NO	A3	NO
Liquefied Petroleum Gas	NO	NO	NO	NO	NO
Butyl acetate	NO	NO	NO	NO	NO
Sealant polymer	NO	NO	NO	NO	NO

**REPRODUCTIVE TOXICITY INFORMATION:** Listed below is information concerning the effects of this product and its components on the human reproductive system.

Mutagenicity: When used as directed, this product is not expected to produce mutagenic effects in humans.  
Embryotoxicity: When used as directed, this product is not expected to produce embryotoxic effects in humans.  
Teratogenicity: When used as directed, this product is not expected to produce teratogenic effects in humans.  
Reproductive Toxicity: When used as directed, this product is not expected to produce reproductive toxicity in humans.

---

## 12. ECOLOGICAL INFORMATION

No data available.

---

## 13. DISPOSAL CONSIDERATIONS

Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations.

---

## 14. TRANSPORTATION INFORMATION

### U.S. DOT (Road or Rail):

Proper Shipping Name: CONSUMER COMMODITY

Hazard Class: ORM-D

ID Number:

Packing Group:

---

## 15. REGULATORY INFORMATION

### ADDITIONAL U.S. REGULATIONS:

EPA REPORTING REQUIREMENTS: The following reporting requirements are applicable to components of this product:

CHEMICAL	SECTION 302 (40 CFR 355, Appendix A)	SECTION 304 (40 CFR Table 302.4)	SECTION 313 (40 CFR 372.65)
Hydrocarbon solvent	NO	NO	NO
Liquefied Petroleum Gas	NO	NO	NO
Sealant polymer	NO	NO	NO

U.S. SARA SECTION 311/312 FOR PRODUCT: Acute health effects; chronic health effects; fire hazard; flammable.

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory.

---

## 16. OTHER INFORMATION

Disclaimer: As the handling and use of products under user's conditions are beyond our control, no warranty, expressed or implied, including, but not limited to merchantability or fitness for a particular use, is made concerning this product. The user assumes all risk of use or handling whether or not in accordance with any directions or suggestions of the supplier. Seller shall not be liable to purchaser or any other person for loss or damages directly or indirectly arising from the use of our products, from breach of any warranty or from any other cause, the exclusive remedy against the seller being to require replacement or repair of defective goods.